

# Efka<sup>®</sup> SI 2722

(old : Efka<sup>®</sup> 2722)



## general

## defoamer

Efka<sup>®</sup> SI 2722 produces rapid de-aeration of solvent-free epoxy and polyurethane compounds so that foam- and blister-free self-leveling coatings can be produced. Efka<sup>®</sup> SI 2722 acts as a leveling agent, giving a smooth surface to the coating.

## chemical nature

solution of defoaming substances containing silicone

## Properties

### physical form

colorless, clear to slightly hazy liquid

### shelf life

The product should be stored in a cool dry place. When kept in its original unopened containers, it will keep up to 4 years.

### typical properties (no supply specification)

solvent	methoxypropylacetate/ alkylbenzene
density at 20 °C (68 °F)	~ 0.91 g/cm <sup>3</sup>
refractive index	~ 1.476
flash point	42 °C (108°F)

## Application

Efka<sup>®</sup> SI 2722 can be used in pigmented or non-pigmented resin systems such as

- solvent-free epoxy systems
- solvent-free polyurethane systems

### recommended concentrations

0.5–1.5% on total formulation

Efka<sup>®</sup> SI 2722 can be incorporated prior to processing. If added subsequently, good distribution should be ensured.

**Safety**

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = registered trademark, ™ = trademark of the BASF Group, unless otherwise noted

BASF SE  
Formulation Additives  
67056 Ludwigshafen, Germany  
[www.dispersions-pigments.basf.com](http://www.dispersions-pigments.basf.com)  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)